

SERIES: PYB20 | DESCRIPTION: DC-DC CONVERTER

FEATURES


- up to 20 W isolated output
- industry standard pinout
- 4:1 input range (9~36 V, 18~75 V)
- smaller package
- single/dual regulated outputs
- 1,500 Vdc isolation
- continuous short circuit, over current protection, over voltage protection
- temperature range (-40~85°C)
- six-sided metal shielding
- efficiency up to 90%



MODEL	input voltage	output voltage	output current		output power max	ripple and noise¹	efficiency
	typ (Vdc)	range (Vdc)	min (mA)	max (mA)	(W)	max (mVp-p)	typ (%)
PYB20-Q24-S3	24	9~36	3.3	250	5000	16.5	100
PYB20-Q24-S5	24	9~36	5	200	4000	20	100
PYB20-Q24-S12	24	9~36	12	84	1667	20	100
PYB20-Q24-S15	24	9~36	15	67	1333	20	100
PYB20-Q24-S24	24	9~36	24	42	834	20	100
PYB20-Q24-D5	24	9~36	±5	±100	±2000	20	100
PYB20-Q24-D12	24	9~36	±12	±42	±834	20	100
PYB20-Q24-D15	24	9~36	±15	±33	±667	20	100
PYB20-Q48-S3	48	18~75	3.3	250	5000	16.5	100
PYB20-Q48-S5	48	18~75	5	200	4000	20	100
PYB20-Q48-S12	48	18~75	12	84	1667	20	100
PYB20-Q48-S15	48	18~75	15	67	1333	20	100
PYB20-Q48-S24	48	18~75	24	42	834	20	100
PYB20-Q48-D5	48	18~75	±5	±100	±2000	20	100
PYB20-Q48-D12	48	18~75	±12	±42	±834	20	100
PYB20-Q48-D15	48	18~75	±15	±33	±667	20	100

Notes: 1. Ripple and noise are measured at 20 MHz BW by "parallel cable" method

PART NUMBER KEY



INPUT

parameter	conditions/description	min	typ	max	units
operating input voltage	24 V input models	9	24	36	Vdc
	48 V input models	18	48	75	Vdc
start-up voltage	24 V input models			9	Vdc
	48 V input models			17.8	Vdc
under voltage shutdown	24 V input models	7.5			Vdc
	48 V input models	16			Vdc
surge voltage	for maximum of 1 second				
	24 V input models	-0.7		50	Vdc
	48 V input models	-0.7		100	Vdc
start-up time	nominal input, constant load		10		ms
filter	pi filter				
CTRL ¹	models ON (CTRL open or connect TTL high level, 2.5-12 Vdc)				
	models OFF (CTRL connect GND or low level, 0-1.2 Vdc)				
	input current (models OFF)	1			mA

Note: 1. CTRL pin voltage is referenced to GND.

OUTPUT

parameter	conditions/description	min	typ	max	units
line regulation	full load, input voltage from low to high	±0.2	±0.5	%	
load regulation	10% to 100% load	±0.5	±1	%	
cross regulation	dual output models: main output 50% load, secondary output from 10% to 100% load			±5	%
voltage accuracy		±1	±3	%	
voltage balance ²	dual output, balanced loads	±0.5	±1	%	
adjustability ³		±10			%
switching frequency	PWM mode, PYB20-Q24-S24	315	345	KHz	
	PWM mode, all other models	300		KHz	
transient recovery time	25% load step change	300	500	µs	
transient response deviation	25% load step change	±3	±5	%	
temperature coefficient	100% load		±0.02		%/°C

Note: 2. For dual output models, unbalanced load can not exceed ±5%. If ±5% is exceeded it may not meet all specifications.
 3. Output trimming available on single output models only.

PROTECTIONS

parameter	conditions/description	min	typ	max	units
short circuit protection	hiccup, continuous, automatic recovery				
over current protection		160			%
over voltage protection	3.3 Vdc output models		3.9		Vdc
	5 Vdc output models		6.2		Vdc
	12 Vdc output models		15		Vdc
	15 Vdc output models		18		Vdc
	24 Vdc output models		30		Vdc

SAFETY AND COMPLIANCE


parameter	conditions/description	min	typ	max	units
isolation voltage	for 1 minute at 1 mA max.	1,500			Vdc
isolation resistance	at 500 Vdc	1,000			MΩ
conducted emissions	CISPR22/EN55022, class A, class B (external circuit required, see Figure 1-b)				
radiated emissions	CISPR22/EN55022, class A, class B (external circuit required, see Figure 1-b)				
ESD	IEC/EN61000-4-2, class B, contact ± 4kV				
radiated immunity	IEC/EN61000-4-3, class A, 10V/m				
EFT/burst	IEC/EN61000-4-4, class B, ± 2kV (external circuit required, see Figure 1-a)				
surge	IEC/EN61000-4-5, class B, ± 2kV (external circuit required, see Figure 1-a)				
conducted immunity	IEC/EN61000-4-6, class A, 3 Vr.m.s				
voltage dips & interruptions	IEC/EN61000-4-29, class B, 0%-70%				
MTBF	as per MIL-HDBK-217F @ 25°C	1,000,000			hours
RoHS compliant	yes				

ENVIRONMENTAL

parameter	conditions/description	min	typ	max	units
operating temperature	see derating curve	-40	85		°C
storage temperature		-55	125		°C
storage humidity	non-condensing	5	95		%
case temperature	at full load, Ta=71°C		105		°C
vibration	10~55 Hz for 30 min. along X, Y and Z axis	10			G

SOLDERABILITY

parameter	conditions/description	min	typ	max	units
hand soldering	1.5 mm from case for 10 seconds		300		°C
wave soldering	see wave soldering profile		260		°C



MECHANICAL

parameter	conditions/description	min	typ	max	units
dimensions	board mount: 50.8 x 25.4 x 11.8 board mount with heatsink: 50.8 x 25.4 x 16.3				mm mm
case material	aluminum alloy				
weight	board mount board mount with heatsink	28	36		g g

MECHANICAL DRAWING

BOARD MOUNT




units: mm[inch]

tolerance: $\pm 0.3[\pm 0.012]$

pin diameter tolerance: $\pm 0.10[\pm 0.004]$

pin height tolerance: $\pm 0.50[\pm 0.020]$

PIN CONNECTIONS		
PIN	Single Output	Dual Output
1	GND	GND
2	Vin	Vin
3	+Vo	+Vo
4	Trim	0V
5	0V	-Vo
6	CTRL	CTRL



BOARD MOUNT WITH HEATSINK




units: mm[inch]

tolerance: $\pm 0.3[\pm 0.012]$


pin diameter tolerance: $\pm 0.10[\pm 0.004]$

pin height tolerance: $\pm 0.50[\pm 0.020]$

PIN CONNECTIONS		
PIN	Single Output	Dual Output
1	GND	GND
2	Vin	Vin
3	+Vo	+Vo
4	Trim	0V
5	0V	-Vo
6	CTRL	CTRL



DERATING CURVES



EMC RECOMMENDED CIRCUIT

Figure 1




Table 1

Recommended external circuit components		
Vin (Vdc)	24	48
FUSE	Choose according to input current	
MOV	S14K35	S14K60
LDM1	56µH	56µH
TVS	SMCJ48A	SMCJ90A
C0	330µF/50V	330µF/100V
C1	1µF/50V	1µF/100V
LDM2	4.7µH	4.7µH
CY1	1nF/2KV	1nF/2KV
CY2	1nF/2KV	1nF/2KV

TEST CONFIGURATION




Figure 2

Table 2

External components	
Lin	4.7µH
Cin	220µF, ESR < 1.0Ω at 100 KHz

Note: Input reflected-ripple current is measured with an inductor Lin and Capacitor Cin to simulate source impedance.

APPLICATION NOTES

1. Recommended circuit

This series has been tested according to the following recommended testing circuit before leaving the factory. This series should be tested under load (see Figure 3). If you want to further decrease the input/output ripple, you can increase the capacitance accordingly or choose capacitors with low ESR (see Table 3). However, the capacitance of the output filter capacitor must be appropriate. If the capacitance is too high, a startup problem might arise. For every channel of the output, to ensure safe and reliable operation, the maximum capacitance must be less than the maximum capacitive load (see Table 4).

Figure 3





Table 3


Single Vout (Vdc)	Cin (μF)	Cout (μF)	Dual Vout (Vdc)	Cin (μF)	Cout ¹ (μF)
3.3	100	470	--	--	--
5	100	470	±5	100	220
12	100	220	±12	100	100
15	100	220	±15	100	100
24	100	100	--	--	--

Note: 1. For each output.

2. Output voltage trimming

Leave open if not used.

Figure 4



Formula for Trim Resistor

$$\text{up: } R_{T\text{up}} = \frac{aR_2}{R_2+a} - R_3 \quad a = \frac{V_{\text{ref}}}{V_{\text{o}'\text{up}} - V_{\text{ref}}} \cdot R_1$$

$$\text{down: } R_{T\text{down}} = \frac{aR_1}{R_1+a} - R_3 \quad a = \frac{V_{\text{o}'\text{down}} - V_{\text{ref}}}{V_{\text{ref}}} \cdot R_2$$

Note: Value for R1, R2, R3, and Vref refer to Table 5
 R_T : Trim Resistor
 a : User-defined parameter, no actual meanings
 $V_{\text{o}'}$: The trim up/down voltage

Table 5

Vout (Vdc)	R1 (KΩ)	R2 (KΩ)	R3 (KΩ)	Vref (V)
3.3	4.801	2.863	15	1.24
5	2.883	2.864	10	2.5
12	10.971	2.864	17.8	2.5
15	14.497	2.864	17.8	2.5
24	24.872	2.863	20	2.5

- Note:
1. Minimum load shouldn't be less than 5%, otherwise ripple may increase dramatically. Operation under minimum load will not damage the converter, however, they may not meet all specifications listed.
 2. Maximum capacitive load is tested at input voltage range and full load.
 3. All specifications are measured at $T_a=25^\circ\text{C}$, humidity<75%, nominal input voltage and rated output load unless otherwise specified.

REVISION HISTORY

rev.	description	date
1.0	initial release	06/26/2013
1.01	updated spec	08/15/2013

The revision history provided is for informational purposes only and is believed to be accurate.



Headquarters
20050 SW 112th Ave.
Tualatin, OR 97062
800.275.4899

Fax 503.612.2383
cui.com
techsupport@cui.com

CUI offers a two (2) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.